# seera L'





## **Dual Voltage Shaver Socket Outlet**



Range of Simply Stylish Wiring Accessories

Designed to provide a competitive, cost effective equivalent range of white moulded accessories with a sleek, slim design creating a moden aesthetic.

Manufactured from Polycarbonate with reinforced interior plates to ensure every product is robust, strong, durable and UV stabilised so that signs of ageing is not a problem.

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB





# **Dual Voltage Shaver Socket Outlet**

### **Product Range**

**Dual Voltage Shaver Socket Outlet** 

**CPC100** 

115/230V Dual Voltage Shaver Socket Outlet



**CPC100** 

Facsimile: 01827 63362


Website: www.scolmore.com






# **Dual Voltage Shaver Socket Outlet**

# Product Dimensional Drawings (mm)



# **Product Wiring Diagram**

CPC100



Errors & Omissions excluded. Specification is subject to change without notice.

V1.0

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB





### **Dual Voltage Shaver Socket Outlet**

Technical Specification	
Dual Voltage Shaver Socket Outlet	
Material Composition	Front Plate: Polycarbonate
	Insert & Base: Polycarbonate
	Live & Neutral Terminals: Brass Plated Steel
	Earth Terminal: Brass
	Terminal Screws: Steel & Yellow Passivated
	Internal Mechanism: Formed Press Brass
	Earth Strap: Mild Steel
Voltage	230V~ 50Hz
<b>Current Rating</b>	20Va at 115V or 230V
Terminal Screw Size	3mm ø
<b>Torque Value</b>	0.4Nm
Cable Size	2 x 1.5mm², 1 x 2.5mm²
Fixing Centres	120.6mm (Vertical)
Back Box Depth	47mm
IP Rating	IP20
Warranty	10 Years
<b>Operational Temperature</b>	-5° to +40°C
Standards	The Low Voltage Directive 2014/35/EU
	BS EN 61559-1 & BS EN 61558-2-5
	CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5 making it safe for use in bathrooms.

#### **Additional Information**

Shaver outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB

Telephone: 01827 63454 Facsimile: 01827 63362 E-mail: sales@scolmore.com, technical@scolmore.com Website: www.scolmore.com



#### **Scolmore International Ltd**

1 Scolmore Park: Landsberg Lichfield Road Industrial Estate Tamworth, Staffordshire B79 7XB

t: 01827 63454 f: 01827 63362

e: sales@scolmore.com

w: www.scolmore.com



### EU DECLARATION OF CONFORMITY

1. Issuer Name Scolmore International Limited

2. Issuer Address 1 Scolmore Park, Landsberg,

> Lichfield Road Industrial Estate. Tamworth, Staffordshire, B79 7XB

3. Object(s) of Declaration Seera Range

> a. *Group* **Dual Voltage Shaver Socket Outlet**

b. *Model No.* CPC100

4. The object of the declaration described above is in conformity with the requirements of the following Legislations:

The Low Voltage Directive 2014/35/EU

5. All products contained within the aforementioned comply with the relevant standards and requirements listed below.

BS EN 61558-2-5: 1998 +A11: 2004

BS EN 61558-1: 1997 +A1: 1998 +A11: 2003

6. I hereby declare that the equipment named above has been designed to comply with the relevant sections of the above referenced specifications. The unit complies with all applicable Essential Requirements of the Directives.

In conjunction with the above all manufacture and process controls are in accordance with ISO 9001:2015.

This declaration has been issued under the sole responsibility of the manufacturer, signed at, for and on behalf of: Scolmore International Limited

Karl Rawlins – Senior Technical Support Engineer







