## seera L'





### Flex Outlet Plates



Range of Simply Stylish Wiring Accessories

Designed to provide a competitive, cost effective equivalent range of white moulded accessories with a sleek, slim design creating a moden aesthetic.

Manufactured from Polycarbonate with reinforced interior plates to ensure every product is robust, strong, durable and UV stabilised so that signs of ageing is not a problem.

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB

## seera L'



## Flex Outlet Plates

Product Ran	ge	
Flex Outlet Plates		
CPC017	20A 3 Terminal Plate With Optional Flex Outlet	
CPC215	45A 3 Terminal Plate With Optional Cable Outlet	





17 CPC215

**Facsimile:** 01827 63362


Website: www.scolmore.com


## seera L'




## Flex Outlet Plates


## **Product Dimensional Drawings (mm)**





## **Product Wiring Diagram**





Errors & Omissions excluded. Specification is subject to change without notice.

V1.0

Facsimile: 01827 63362

Website: www.scolmore.com

Scolmore International Ltd, 1 Scolmore Park, Landsberg, Lichfield Road Ind. Estate, Tamworth, Staffordshire, B79 7XB





## Flex Outlet Plates

Technical Specification			
Flex Outlet Plates			
Material Composition	Front Plate: Polycarbonate		
	Insert & Base: Polycarbonate		
	Terminals: Brass		
	Terminal Screws: Steel & Yellow Passivated		
	Earth Strap: Mild Steel		
Voltage	250V~ 50Hz		
<b>Current Rating</b>	20A	45A	
Terminal Screw Size	5mm ø	8mm ø	
Torque Value	1.8Nm	2.5Nm	
Terminal Capacity	6mm <sup>2</sup>	10mm <sup>2</sup>	
Cord Grip Anchorage	14mm <sup>2</sup>	10mm <sup>2</sup>	
Cable Outlet Dimensions	10mm x 10mm	18.5mm x 20mm	
Fixing Centres	60.3mm		
Back Box Depth	35mm		
Warranty	10 Years		
Operational Temperature	-5° to +40°C		
Standards	BS 5733: 2010 +A1: 2014		

#### **Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Facsimile: 01827 63362

Website: www.scolmore.com



#### **Scolmore International Ltd**

1 Scolmore Park: Landsberg Lichfield Road Industrial Estate Tamworth, Staffordshire B79 7XB

t: 01827 63454 f: 01827 63362

e: sales@scolmore.com

w: www.scolmore.com

# seera

### **EU DECLARATION OF CONFORMITY**

1. Issuer Name Scolmore International Limited

2. Issuer Address 1 Scolmore Park, Landsberg,

Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB

3. Object(s) of Declaration Seera Range

a. *Group* Flex Outlet Platesb. *Model No.* CPC017 & CPC215

- 4. The object of the declaration described above is in conformity with the requirements of the following Legislations:
- 5. All products contained within the aforementioned comply with the relevant standards and requirements listed below.

BS 5733: 2010 +A1: 2014

6. I hereby declare that the equipment named above has been designed to comply with the relevant sections of the above referenced specifications. The unit complies with all applicable Essential Requirements of the Directives.

In conjunction with the above all manufacture and process controls are in accordance with ISO 9001:2015.

This declaration has been issued under the sole responsibility of the manufacturer, signed at, for and on behalf of: Scolmore International Limited

Karl Rawlins - Senior Technical Support Engineer







